



Fibre Termination Units are used for termination and management of Fibre backbone and equipment cables in Central Office and bulk fibre distribution systems. It serves as the interface between field cables and equipments. Cables may be terminated direct or after splicing. Provision has been made for internal fibre management by cable spooling with minimum bend radius and stackable splice trays. Rack mounted versions are designed for flange mounting on 19 inch racks.

Applications

- ❖ Telecom Networks

Sheet Metal Box

Fabricated from carbon steel , pre treated and painted with enamel or powder coated to ensure corrosion resistance. Standard mounting on 19 inch Finished in Standard colours of Siemens Gray or black, with other colours on request.

Product features

- ❖ Number of fibers up to 96F
- ❖ Pigtail : 1.5m 900um G657A2 single mode LC/APC
- ❖ 12 color pigtail
- ❖ Provision for cable anchoring.
- ❖ Stackable splice tray.
- ❖ Multiple connector options. Easy inter-changeability.
- ❖ Cable entry from rear side. Radius controlled cable routing.
- ❖ Draw out or fixed termination tray options.
- ❖ Front Access to cable connectors.
- ❖ Heat resistant, high impact plastic parts.
- ❖ Screen printed panels for easy identification.

Optical Performane

- ❖ Insertion Loss : 0.2dB
- ❖ Back Reflection (APC) : >60dB

Description	Model Number
72F ODF LC/APC 2U	FR5MA53LCAX-2S4-SRH
60F ODF LC/APC 2U	FR6MA53LCAX-2S4-SRH
96F ODF LC/APC 2U	FR9MA54LCAX-2S4-SRH